

AMENDMENT TO THE CLAIMS:

1. (currently amended) A filter assembly for medical and laboratory use comprising a housing, the housing comprising:

a plastic cover having a perimeter and comprising an inlet;

a bottom part having an underside and comprising an outlet; and

5 a plurality of plastic spring levers distributed around the perimeter circumference of the cover and unitarily formed with the plastic cover, the spring levers rotatable ~~at~~ on pivot points and including hook-shaped projections projecting inwardly relative to the cover perimeter on one side of the pivot points and actuation flaps on the other side of the pivot points, wherein the spring levers are resiliently pre-tensioned to
10 direct the hook-shaped projections inwardly relative to the cover perimeter and the hook-shaped projections releasably overlapping and attaching to ~~connectable with~~ the bottom part underside upon actuation of the actuation flaps, wherein the filter assembly is adapted to clamp a filter membrane between the cover and the bottom part in a fluid-tight manner when the hook-shaped projections overlap and attach to ~~connect with~~ the
15 bottom part underside.

2. (currently amended) A filter assembly according to claim 1, wherein the cover has a circumference and the bottom part comprises a bottom rim, and wherein the hook-shaped projections overlap the bottom rim of the bottom part to releasably attach thereto, and wherein the spring levers are adapted to rotate about the pivot points upon
20 actuation of the upwardly projecting actuation flaps in a radial direction relative to the circumference of the cover.

3. (currently amended) A filter assembly according to claim 2, ~~wherein the spring levers and the cover are formed unitarily of plastic, and~~ wherein the spring levers are molded onto flaps laterally projecting from the cover, which flaps form the
25 pivot points of the spring levers.

4. (original) A filter assembly according to claim 3, wherein the plurality of spring levers comprises three spring levers distributed equidistantly around the circumference of the cover.

5. (original) A filter assembly according to claim 4, further comprising an annular seal between the cover and the bottom part, wherein the cover comprises an annular channel and a free annular space, and wherein the bottom part comprises an annular projection engaging the free annular space, wherein the annular seal is disposed in the annular channel.

6. (original) A filter assembly according to claim 5, wherein a disk-shaped supporting body for the filter membrane is disposed in a recess of the bottom part, and wherein the recess comprises supporting ribs surrounding the outlet.

7. (original) A filter assembly according to claim 6, wherein the supporting body comprises a porous material.

8. (original) A filter assembly according to claim 7, wherein the filter membrane comprises a lateral tongue extending from the closed housing.

9. (original) A filter assembly according to claim 8, wherein the bottom part comprises an annular channel defined in part by an exterior wall and a bottom, which exterior wall is overlapped by the hook-shaped projections and wherein the bottom of the annular channel is positioned generally at a same height as a height of the bottom of the recess.

10. (original) A filter assembly according to claim 9, wherein the cover and the bottom part each comprises a recess for the passage of the tongue of the filter membrane.

11. (original) A filter assembly according to claim 5, wherein the filter membrane comprises a lateral tongue extending from the closed housing.

5 12. (original) A filter assembly according to claim 11, wherein the bottom part comprises an annular channel defined in part by an exterior wall and a bottom, which exterior wall is overlapped by the hook-shaped projections and wherein the bottom of the annular channel is positioned generally at a same height as a height of the bottom of the recess.

13. (original) A filter assembly according to claim 12, wherein the cover and the bottom part each comprises a recess for the passage of the tongue of the filter membrane.

10 14. (original) A filter assembly according to claim 5, wherein the bottom part comprises an annular channel defined in part by an exterior wall and a bottom, which exterior wall is overlapped by the hook-shaped projections and wherein the bottom of the annular channel is positioned generally at a same height as a height of the bottom of the recess.

15 15. (original) A filter assembly according to claim 14, wherein the cover and the bottom part each comprises a recess for the passage of a tongue of the filter membrane.

16. (currently amended) A filter assembly according to claim 1, wherein the cover has a circumference and the plurality of spring levers comprises three spring levers distributed equidistantly around the circumference of the cover.

20 17. (original) A filter assembly according to claim 16, further comprising an annular seal between the cover and the bottom part, wherein the cover comprises an annular channel and a free annular space, and wherein the bottom part comprises an annular projection engaging the free annular space, wherein the annular seal is disposed in the annular channel.

25 18. (original) A filter assembly according to claim 17, further comprising an annular projection such that with the housing closed a circumferential rim of the filter membrane is clamped between the annular seal and a contact surface of the bottom part,

wherein a disk-shaped supporting body for the filter membrane is disposed in a recess of the bottom part, and wherein the recess comprises supporting ribs surrounding the outlet.

5 19. (original) A filter assembly according to claim 18, wherein the supporting body comprises a porous material.

20. (original) A filter assembly according to claim 19, wherein the filter membrane comprises a lateral tongue extending from the closed housing.

10 21. (original) A filter assembly according to claim 20, wherein the bottom part comprises an annular channel defined in part by an exterior wall and a bottom, which exterior wall is overlapped by the hook-shaped projections and wherein the bottom of the annular channel is positioned generally at a same height as a height of the bottom of the recess.

15 22. (original) A filter assembly according to claim 21, wherein the cover and the bottom part each comprises a recess for the passage of the tongue of the filter membrane.

23. (original) A filter assembly according to claim 17, wherein the filter membrane comprises a lateral tongue extending from the closed housing.

20 24. (original) A filter assembly according to claim 23, wherein the bottom part comprises an annular channel defined in part by an exterior wall and a bottom, which exterior wall is overlapped by the hook-shaped projections and wherein the bottom of the annular channel is positioned generally at a same height as a height of the bottom of the recess.

25 25. (original) A filter assembly according to claim 24, wherein the cover and the bottom part each comprises a recess for the passage of the tongue of the filter membrane.

26. (original) A filter assembly according to claim 17, wherein the bottom part comprises an annular channel defined in part by an exterior wall and a bottom, which exterior wall is overlapped by the hook-shaped projections and wherein the bottom of the annular channel is positioned generally at a same height as a height of the bottom of the recess.

27. (original) A filter assembly according to claim 26, wherein the cover and the bottom part each comprises a recess for the passage of a tongue of the filter membrane.

28. (currently amended) A filter assembly according to claim 1, ~~wherein the spring levers and the cover are formed unitarily of plastic, and~~ wherein the spring levers are molded onto members ~~flaps~~ laterally projecting from the cover, which flaps form the pivot points of the spring levers.

29. (currently amended) A filter assembly according to claim 28, wherein the cover has a circumference and the plurality of spring levers comprises three spring levers distributed equidistantly around the circumference of the cover.

30. (original) A filter assembly according to claim 29, further comprising an annular seal between the cover and the bottom part, wherein the cover comprises an annular channel and a free annular space, and wherein the bottom part comprises an annular projection engaging the free annular space, wherein the annular seal is disposed in the annular channel.

31. (original) A filter assembly according to claim 30, further comprising an annular projection such that with the housing closed a circumferential rim of the filter membrane is clamped between the annular seal and a contact surface of the bottom part, wherein the bottom part includes a recess, and wherein the recess comprises supporting ribs surrounding the outlet.

32. (original) A filter assembly according to claim 31, wherein the supporting body comprises a porous material.

33. (original) A filter assembly according to claim 32, wherein the filter membrane comprises a lateral tongue extending from the closed housing.

34. (original) A filter assembly according to claim 33, wherein the bottom part comprises an annular channel defined in part by an exterior wall and a bottom, which exterior wall is overlapped by the hook-shaped projections and wherein the bottom of the annular channel is positioned generally at a same height as a height of the bottom of the recess.

35. (original) A filter assembly according to claim 34, wherein the cover and the bottom part each comprises a recess for the passage of the tongue of the filter membrane.

36. (original) A filter assembly according to claim 1, further comprising an annular seal between the cover and the bottom part, wherein the cover comprises an annular channel and a free annular space, and wherein the bottom part comprises an annular projection engaging the free annular space, wherein the annular seal is disposed in the annular channel.

37. (original) A filter assembly according to claim 36, wherein the filter membrane comprises a lateral tongue extending from the closed housing.

38. (original) A filter assembly according to claim 37, wherein the bottom part comprises an annular channel defined in part by an exterior wall and a bottom, which exterior wall is overlapped by the hook-shaped projections and wherein the bottom of the annular channel is positioned generally at a same height as a height of the bottom of the recess.

39. (original) A filter assembly according to claim 38, wherein the cover and the bottom part each comprises a recess for the passage of a tongue of the filter membrane.

40. (original) A filter assembly according to claim 36, further comprising an annular projection such that with the housing closed a circumferential rim of the filter

membrane is clamped between the annular seal and a contact surface of the bottom part, wherein the bottom part includes a recess, and wherein the recess comprises supporting ribs surrounding the outlet.

5 41. (original) A filter assembly according to claim 40, wherein the supporting body comprises a porous material.

42. (original) A filter assembly according to claim 41, wherein the filter membrane comprises a lateral tongue extending from the closed housing.

10 43. (original) A filter assembly according to claim 42, wherein the bottom part comprises an annular channel defined in part by an exterior wall and a bottom, which exterior wall is overlapped by the hook-shaped projections and wherein the bottom of the annular channel is positioned generally at a same height as a height of the bottom of the recess.

15 44. (original) A filter assembly according to claim 43, wherein the cover and the bottom part each comprises a recess for the passage of the tongue of the filter membrane.

45. (original) A filter assembly according to claim 1, wherein the filter membrane comprises a lateral tongue extending from the closed housing.

20 46. (original) A filter assembly according to claim 45, wherein the bottom part comprises an annular channel defined in part by an exterior wall and a bottom, which exterior wall is overlapped by the hook-shaped projections and wherein the bottom of the annular channel is positioned generally at a same height as a height of the bottom of the recess.

25 47. (original) A filter assembly according to claim 46, wherein the cover and the bottom part each comprises a recess for the passage of the tongue of the filter membrane.

5 48. (original) A filter assembly according to claim 1, wherein the bottom part comprises an annular channel defined in part by an exterior wall and a bottom, which exterior wall is overlapped by the hook-shaped projections and wherein the bottom of the annular channel is positioned generally at a same height as a height of the bottom of the recess.

49. (original) A filter assembly according to claim 48, wherein the cover and the bottom part each comprises a recess for the passage of a tongue of the filter membrane.

10 50. (currently amended) A filter assembly for medical and laboratory use and adapted to receive a filter media sheet, the filter assembly comprising:

a plastic cover having a perimeter and comprising an inlet;
a bottom part having an underside and comprising an outlet;
a means for supporting the filter media sheet; and
a plurality of plastic spring levers distributed around the perimeter
15 ~~circumference~~ of the cover and unitarily formed with the plastic cover, the spring levers rotatable ~~at~~ on pivot points and including hook-shaped projections oriented inwardly relative to the perimeter and on one side of the pivot points and actuation flaps on the other side of the pivot points, wherein the spring levers are resiliently pre-tensioned to direct the hook-shaped projections inwardly relative to the cover perimeter and the
20 hook-shaped projections releasably overlapping and attaching to ~~connectable with~~ the bottom part underside upon actuation of the flaps, wherein the filter assembly is adapted to clamp a filter media sheet between the cover and the bottom part in a fluid-tight manner when the hook-shaped projections overlap and attach to ~~connect with~~ the bottom part underside.

25 51. (currently amended) A filter assembly according to claim 50, wherein the cover has a circumference and the bottom part comprises a bottom rim, and wherein the hook-shaped projections overlap the bottom rim of the bottom part to releasably attach thereto, and wherein the spring levers are adapted to rotate about the pivot points upon

actuation of the upwardly projecting actuation flaps in a radial direction relative to the circumference of the cover.

52. (original) A filter assembly according to claim 50, further comprising an annular seal between the cover and the bottom part, wherein the cover comprises an annular channel and a free annular space, and wherein the bottom part comprises an annular projection engaging the free annular space, wherein the annular seal is disposed in the annular channel.

53. (original) A filter assembly according to claim 50, wherein the means for supporting the filter media comprises a disk-shaped supporting body for the filter media sheet disposed in a recess of the bottom part, and wherein the recess comprises supporting ribs surrounding the outlet.

54. (original) A filter assembly according to claim 50 wherein the means for supporting the filter media comprises a plurality of ribs.

55. (original) A filter assembly according to claim 50, wherein the filter media sheet comprises a lateral tongue extending from the closed housing.

56. (original) A filter assembly according to claim 55, wherein the cover and the bottom part each comprises a recess for the passage of the tongue of the filter media sheet.

57. (original) A filter assembly according to claim 51, wherein the means for supporting the filter media comprises a disk-shaped supporting body for the filter media sheet disposed in a recess of the bottom part, and wherein the recess comprises supporting ribs surrounding the outlet.

58. (original) A filter assembly according to claim 51 wherein the means for supporting the filter media comprises a plurality of ribs.

59. (original) A filter assembly according to claim 52, wherein the means for supporting the filter media comprises a disk-shaped supporting body for the filter media

sheet disposed in a recess of the bottom part, and wherein the recess comprises supporting ribs surrounding the outlet.

60. (original) A filter assembly according to claim 52 wherein the means for supporting the filter media comprises a plurality of ribs